



Floor standing unit

FVQ-C



Seasonal Smart Seasonal Classic



Home leave operation



Vertical auto swing

For commercial spaces with high ceilings

- › Ideal solution for commercial spaces with no or narrow false ceilings
- › Can easily be installed in both new and refurbishment projects
- › Very efficient for use in rooms with high ceilings
- › Decrease of temperature variation by automatic fan speed selection or freely selectable 3-step fan speed.
- › Improved comfort as a result of better airflow distribution from the vertical out blow which allows manual adjustment of air outlet blades at the top of the unit. Selectable horizontal out blow to better suit the layout of the room (via BRC1E52).
- › No optional adapter needed for DIII-connection, link your unit into the wider building management system.

FVQ-C + RZQG-L9V1/L(8)Y1, RZQSG-L3/9V1/L(8)Y1



Indoor unit		FVQ	71C	100C	125C	140C
Casing	Colour	Fresh White				
Dimensions	Unit HeightxWidthxDepth	mm	1,850x600x270	1,850x600x350		
Sound power level	Cooling/Heating	dB(A)	55/55	62/62	63/63	65/65
Sound pressure level	Cooling	High/Nom./Low	43/41/38	50/47/44	51/48/46	53/51/48
	Heating	High/Nom./Low	43/41/38	50/47/44	51/48/46	53/51/48
Control systems	Wired remote control	BRC1D52 / BRC1E52A/B				



Combination with Seasonal Smart outdoor units ensure high quality, optimal comfort, flexible installation and highest efficiency values.





Combination with Seasonal Classic ensures good value for money for all types of commercial applications.

Efficiency data		FVQ + RZQG/RZQSG	71C + 71L9V1	100C + 100L9V1	125C + 125L9V1	140C + 140L9V1	71C + 71L8Y1	100C + 100L8Y1	125C + 125L8Y1	140C + 140L8Y1	71C + 71L3V1	100C + 100L9V1	125C + 125L9V1	140C + 140L9V1	100C + 100L8Y1	125C + 125L8Y1	140C + 140L8Y1	
Cooling capacity	Nom.	kW	6.8	9.5	12.0	13.4	6.8	9.5	12.0	13.4	6.8	9.5	12.0	13.4	6.8	9.5	12.0	13.4
Heating capacity	Nom.	kW	7.5	10.8	13.5	15.5	7.5	10.8	13.5	15.5	7.5	10.8	13.5	15.5	7.5	10.8	13.5	15.5
Power input	Cooling	Nom.	2.02	2.49	3.74	4.17	2.02	2.49	3.74	4.17	2.12	2.96	4.27	4.45	2.96	4.27	4.45	
	Heating	Nom.	2.06	2.61	3.65	4.30	2.06	2.61	3.65	4.30	2.08	2.99	3.96	4.54	2.99	3.96	4.54	
Seasonal efficiency (according to EN14825)	Cooling	Energy label	A++	A+	-	-	A++	A+	-	-	A	-	-	-	A	-	-	
		Pdesign	6.80	9.50	12.00	-	6.8	9.5	12	-	6.80	9.50	12.00	-	9.5	12	-	
		SEER	6.31	5.61	-	-	6.31	5.61	-	-	5.50	-	-	-	5.5	-	-	
	Annual energy consumption	kWh	378	593	749	-	378	593	749	-	433	605	764	-	605	764	-	
	Heating (Average climate)	Energy label	A+	A	-	-	A+	A	-	-	A	A+	A	-	A+	A	-	
Pdesign		6.33	11.30	-	-	6.33	11.3	-	-	6.33	7.60	7.60	-	7.6	-	-		
SCOP		4.05	4.20	3.87	-	4.05	4.2	3.87	-	3.86	4.01	3.85	-	4.01	3.85	-		
Annual energy consumption	kWh	2,189	3,767	4,088	-	2,189	3,767	4,088	-	2,296	2,654	2,764	-	2,654	2,764	-		
Piping connections	Liquid	OD	9.52															
	Gas	OD	15.9															
Nominal efficiency	EER		3.37	3.81	3.21		3.37	3.81	3.21		3.21	2.81	3.01		3.21	2.81	3.01	
	COP		3.64	4.14	3.70	3.61	3.64	4.14	3.70	3.61	3.61	3.41	3.41		3.61			
	Annual energy consumption	kWh	1,010	1,245	1,870	2,085	1,010	1,245	1,870	2,085	1,060	1,480	2,135	2,225	1,480	2,135	2,225	
	Energy label	Cooling	A			-	A			-	A			-	A	C	-	
	Heating	A			-	A			-	A	B	-	A	B	-	-		

Outdoor unit		RZQG/RZQSG	71L9V1	100L9V1	125L9V1	140L9V1	71L8Y1	100L8Y1	125L8Y1	140L8Y1	71L3V1	100L9V1	125L9V1	140L9V1	100L8Y1	125L8Y1	140L8Y1
Dimensions	Unit HeightxWidthxDepth	mm	990x940x320	1,430x940x320			990x940x320	1,430x940x320			770x900x320	990x940x320		1,430x940x320	990x940x320		1,430x940x320
Sound power level	Cooling	dB(A)	64	66	67	69	64	66	67	69	65	70		69	69	70	69
Sound pressure level	Cooling	Nom./Silent operation	48/-	50/-	51/-	52/-	48/-	50/-	51/-	52/-	49/47	53/-	54/-	53/-	54/-	53/-	53/-
	Heating	Nom.	50	52	53		50	52	53		51	57	58	54	57	58	54
	Night quiet mode	Level 1	43	45			43	45			-	49					
Operation range	Cooling	Ambient	-15~50														
	Heating	Ambient	-20~15.5														
Refrigerant	Type/GWP		R-410A/2,087.5														
	Charge	kg/TCO _{Eq}	2.9/6.1	4/8.4			2.9/6.1	4/8.4			2.75/5.7	2.9/6.1	4/8.4	2.9/6.1	4/8.4	3N~/5.0	3/80-415
Power supply	Phase / Frequency / Voltage	Hz / V	1~/50/220-240			3N~/50/380-415			1~/50/220-240			3N~/50/380-415					

Contains fluorinated greenhouse gases (1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN15-108 02/15



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.